




M-LL/L/S Nut

Benefits

- Reliable first time assembly.
- High sealing efficiency for cutting ring technology.
- High nominal pressure L Series - up to 600 bar S Series - up to 800 bar.
- Available in stainless steel body & nut on request * WalproX stainless ring now available.

Features

- Two edge cutting ring.
- Cone stop limit to prevent over tightening.
- 6mm to 42mm OD tube sizes in (L) light and (S) heavy series.
- Best cutting ring pressure performance.



Primary Item No	Tube O/D	Part No	M Thread	l ₁ mm	S ₂ A/F mm	Max WP Bar
5070223	4	M4LL	M8x1	11	10	100
5070225	6	M6L	M12x1,5	14,5	14	500
5070226	6	M6LL	M10x1	11,5	12	100
5070227	6	M6S	M14x1,5	16,5	17	800
5070228	8	M8L	M14x1,5	16,6	17	500
5070229	8	M8LL	M12x1	12	14	100
5070230	8	M8S	M16x1,5	16,5	19	800
5070208	10	M10L	M16x1,5	15,5	19	500
5070209	10	M10S	M18x1,5	17,5	22	800
5070210	12	M12L	M18x1,5	15,5	22	400
5070211	12	M12S	M20x1,5	17,5	24	630
5070212	14	M14S	M22x1,5	20,5	27	630
5070213	15	M15L	M22x1,5	17	27	400
5070214	16	M16S	M24x1,5	20,5	30	630
5070215	18	M18L	M26x1,5	18	32	400
5070216	20	M20S	M30x2	24	36	420
5070217	22	M22L	M30x2	20	36	250
5070218	25	M25S	M36x2	27	46	420
5070219	28	M28L	M36x2	21	41	250
5070220	30	M30S	M42x2	29	50	420
5070221	35	M35L	M45x2	24	50	250
5070222	38	M38S	M52x2	32,5	60	420
5070224	42	M42L	M52x2	24	60	250

Supplied By

Primary Fluid Power Limited
Caddick Road
Knowsley Business Park
L34 9HP
Tel No. +44(0)151 632 9500
Fax No. +44(0)151 548 9896
www.PrimaryFP.co.uk